

PX 8A

Active coaxial point source

PRODUCT FEATURES


- High-performance multi-purpose active coaxial speaker
- Equipped with 1000 W Class D amplifier and low-noise DSP
- Three presets for different usage scenarios
- Analog and digital signal input options
- 120° x 100° coverage pattern (rotatable)

APPLICATIONS

Thanks to its plug-and-play design, compact construction, and flexible connection options, the PX series can be widely applied in many small- to medium-scale portable sound reinforcement applications — including live performances, exhibition sound reinforcement, distributed fill, and stage monitoring, making it a reliable choice for modern audio applications.



PRODUCT DRAWING



PRODUCT DESCRIPTION

The PX 8A is a compact multipurpose active coaxial two-way loudspeaker, equipped with an 8" LF / 1" exit HF coaxial driver, capable of delivering clear, balanced sound quality with wide, controlled coverage. The coaxial design brings the LF and HF sections into a coincident "point source", eliminating the off-axis frequency response variations associated with non-coaxial designs, ensuring a consistently excellent listening experience.

As a self-powered speaker, the PX 8A features a built-in two-channel Class D amplifier delivering up to 500 W LF + 500 W HF to the drive units. Following SE's familiar plug-and-play design, the PX 8A supports analogue or AES digital audio input and loop-through. The built-in scene presets can meet the low-frequency demands of different environments, and its switch-mode power supply automatically adapts to global mains voltages from 100-240 V, 50/60 Hz, and includes short-circuit, over-temperature, and over-current protection. Ensuring a consistently excellent listening experience.

Thanks to its rugged yet lightweight design and flexible connection options, the PX 8A can be widely applied in many small- to medium-scale portable sound reinforcement applications — including exhibition sound reinforcement, distributed front-fill under balconies, compact stage monitors, and more.

SAFETY NOTE Please observe the operating instructions as well as the applicable regulation-sand rules for safe use and operation.

¹ Measured with the FLAT preset
² Measured with 12 dB Crest factor Pink Noise, 1m, whole space
³ Total power value is the sum of all individual channel output power
⁴ According to IHF-A-202 Standard
 All product specifications are subject to change without notice.

SPECIFICATIONS

ACOUSTICAL	
Frequency range (-3 dB) ¹	80 Hz - 17 kHz
Frequency range (-6 dB) ¹	73 Hz - 18 kHz
Coverage angles[H x V]	120° x 100°
Maximum Peak SPL ²	123 dB
System type	2-way
Crossover frequency	1.7 kHz
Transducers	LF: 1 x 8" drivers (2" voice coil) HF: 1 x 1" compression driver (1.75" voice coil)
Enclosure type	Vented box
AMPLIFICATION	
Type	2 channel, class-D with SMPS
Total power ³	1000 W
Output power ⁴	LF: 500 W HF: 500 W
Protection	Short circuit, overheating, overcurrent
Connectors	Input signal: balanced XLR 3-pin female Link output: balanced XLR 3-pin male Power input: powerCON® 20A Power link output: powerCON® 20A
Wiring	Pin layout XLR: Pin 2: Signal+; Pin 3: Signal-; Pin 1: Shield Pin layout powerCON®: Pin N: Neutral; Pin L: Conductor; Pin E: Earth, Ground
Operating voltage range	MAINS IN: 100-120V~/50-60 Hz, 20 A MAX./2.6 A UNIT 220-240V~/50-60 Hz, 16 A MAX./1.3 A UNIT MAINS OUT: 100-120V~/50-60 Hz, 17.4 A MAX 220-240V~/50-60 Hz, 14.7 A MAX
Input sensitivity	0 dBu
DSP	96 kHz/24 bit with extended dynamics Processing latency: 1.1 ms
Processing	Crossover, Limiter, EQ, Level, Low noise AD-DA
User controls	8-position level control (-10, -6, -5, -4, -3, -2, -1, 0) 3-position switch for EQ setting: FLAT, WALL, SAT Input signal mode: Analog, AES Digital (A, B, A+B)
MECHANICAL	
Product dimensions [H x W x D]	380 x 246 x 224 mm
Net weight	10.3 kg
Packaging dimensions [H x W x D]	473 x 325 x 303 mm
Total weight	11.5 kg
Cabinet	15 mm plywood
Cabinet finishing	black polyurea coating
Grille	Powder coated perforated steel with acoustic and dust-proof fabric
Hardware	12 x M8 rigging points 1 x wooden handle 1 x 36 mm pole mounting hole
ACCESSORIES	
Wall Mounting Bracket	WMB75
Flight Case	se PX 8A FC
Transport cover	se PX 8A TC